



# UNIVERSAL

## Multipurpose undercoat for enamels

**RIALTO UNIVERSAL** is composed of special resins and special additives in a solvent.

### PROPERTIES

**RIALTO UNIVERSAL** is marked by and stands out for the following characteristics:

- it protects treated surfaces from corrosion
- it has excellent weather-resistance
- it dries fast
- it has excellent surface adherence
- it can be painted over with solvent-based products

### PURPOSES

**RIALTO UNIVERSAL** is ideal as a priming treatment for exterior and interior surfaces.

- It can be applied to:
  - iron
  - sheet zinc
  - aluminum
  - steel
  - wood
  - wall
  - synthetic products (PVC panels, polyester, polyamides, etc.)

### COVERING CAPACITY

Average covering capacity is 10 m<sup>2</sup>/l (45 sq.yd/gal) applied by brush or roller and 7 m<sup>2</sup>/l (31 sq.yd/gal) applied by spray, but it may vary depending on the nature of the surface.

### PACKAGING

**RIALTO UNIVERSAL** is available in 0.75 l and 2.5 l containers.

### COLOR RANGE

**RIALTO UNIVERSAL** is available in the following colors: red, gray, and white.

### WORKING INSTRUCTIONS

- make sure the surface is completely dry and free of grease stains, dust or any other kind of dirt. Remove rust or paint peeling from the surface
- grease stains and other kind of dirt on zinc or aluminum surfaces should be removed by wash with nitro-thinner
- clean thoroughly wood and iron surfaces to be painted, remove any loose material and if necessary patch
- clean thoroughly surfaces to be painted and if necessary patch or level off
- clean thoroughly synthetic surfaces, sand superficially and finish off with alcohol or turpentine on damaged sections
- when applying by brush or roller, use undiluted product. For application by spray dilute to 15-20% with nitro-thinner (nozzle diameter: 1.5-2 mm; pressure: 2.5-3.5 atm)
- average dust free drying time: 30-40 min but it may vary depending on absorption of the substrate, temperature and humidity.
- average touch-free drying time: 1 hour
- resistant to frost during drying process
- allow at least 2 hours before starting to apply the enamel paint **RIALTO GLAZER**
- possible dried product stains can be removed with a rag soaked in turpentine
- insure adequate ventilation during application of the product in small environments
- store product tightly closed in a cool and dry place away from naked flame
- dispose of product with care
- dispose of waste through authorized waste disposal services

### REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

#### **RIALTO GLAZER**

For further help or information regarding the products in the **RIALTO** range contact your local dealer.

Every care has been taken to ensure that the information provided in this technical data sheet is accurate. **Harpo** is unable to guarantee results as it has no control over the conditions under which its products are applied.

